

## WHEELS

Product group	Wheels
Item number	10000742
Valid wheel size	520 / 85 R 46
Brand	Alliance
Tread pattern	Agristar 375
Valid rim size	DW 18 L x 46
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	5800
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	440,93
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15227430
LI / SI / PR	173 A8 / 169 D
Load capacity 1 [kg]	6500
Speed 1 [km/h].	40
Load capacity 2 [kg]	5800
Speed 2 [km/h].	65
Maximum air pressure [bar].	3,20
TL/TT	TL
Tyre colour	Black

E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	542
Stat. radius (SLR) [mm]	956
Speed Radius Index (SRI)	1025
Rolling circumference [mm].	6284
Tread depth (mm)	60,0
Number of lugs	23x2
Tyre capacity 75% [ltr.]	580
Assembly Item no. Rim	• 39123177
Load capacity of rim 1 [kg]	7120
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	15

Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade