

TYRES

Product group	Tyres
Item number	10000921
Valid tyre size	480 / 70 R 34
LI / SI / PR	152 A8 / 149 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor





Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.



Technical Informations

Item number	10000921
EAN	8903094071029
Valid tyre size	480 / 70 R 34
LI / SI / PR	152 A8 / 149 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor
Carcass properties	E-Ready
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	132,49
Recommended rim size	W15L
Permitted rim size	W14L, W16L
Maximum air pressure [bar].	2,40
Section width (mm)	479
Tread width (mm)	454
Outer diameter of tyre [mm].	1580
Stat. radius (SLR) [mm]	723
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4748
Tread depth (mm)	49,0
Number of lugs	23x2
E-Ready	Yes

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		2,40	
149 D	3250	65		2,40	