

## **TYRES**

Product group	Tyres
Item number	10000966
Valid tyre size	520 / 70 R 38
LI / SI / PR	153 A8 / 150 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor





## Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.



## **Technical Informations**

Item number	10000966
EAN	8903094070725
Valid tyre size	520 / 70 R 38
LI / SI / PR	153 A8 / 150 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor
Carcass properties	E-Ready
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	167,93
Recommended rim size	W16L
Permitted rim size	W15L, W18L
Maximum air pressure [bar].	1,60
Section width (mm)	516
Tread width (mm)	500
Outer diameter of tyre [mm].	1749
Stat. radius (SLR) [mm]	795
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5239
Tread depth (mm)	53,0
Number of lugs	23x2
E-Ready	Yes

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40		1,60	
150 D	3350	65		1,60	