

## WHEELS

Product group	Wheels
Item number	10001138
Valid wheel size	750 / 65 R 26
Brand	Alliance
Tread pattern	360
Valid rim size	DW 25 B x 26
Rim connection	12/371/425
Bolt hole design	A3
Offset (mm)	-70
Rim colour	Anthrazit
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	352,15
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15226739
LI / SI / PR	173 A8 / 170 B
Load capacity 1 [kg]	6500
Speed 1 [km/h].	40
Load capacity 2 [kg]	6000
Speed 2 [km/h].	50
Maximum air pressure [bar].	3,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
TRA Code	R1-W
Antistatic	No
Direction	Right
ECE regulation number	ECE 106
Section width (mm)	751
Stat. radius (SLR) [mm]	727.00
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4942.00
Tread depth (mm)	56,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	638.25
Assembly Item no. Rim	• 10000696
Load capacity of rim 1 [kg]	7300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6100
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Type of drive	Towed axle
Number of bolt holes	12
hub hole diameter [mm].	371
Bolt hole circle diameter [mm]	425
Bolt hole diameter [mm]	27.0
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18

Rim material	steel
RAL	RAL7016
Valve seat	External Valve
Disc thickness [mm]	15.0
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade