

## WHEELS

|                                   |               |
|-----------------------------------|---------------|
| Product group                     | Wheels        |
| Item number                       | 10001139      |
| Valid wheel size                  | 750 / 65 R 26 |
| Brand                             | Alliance      |
| Tread pattern                     | 360           |
| Valid rim size                    | DW 25 B x 26  |
| Rim connection                    | 12/371/425    |
| Bolt hole design                  | A3            |
| Offset (mm)                       | -70           |
| Rim colour                        | Anthrazit     |
| Load capacity complete wheel [kg] | 6500          |
| Speed complete wheel [km/h]       | 40            |
| Nettogewicht [kg] (gültig)        | 352,15        |
| RDA (Reifendruckregelanlage)      | No            |
| RDKS (Reifendruckkontrollsystem)  | No            |



## Technical Informations

|                             |                |
|-----------------------------|----------------|
| Assembly Item no. Tyres     | • 15226739     |
| LI / SI / PR                | 173 A8 / 170 B |
| Load capacity 1 [kg]        | 6500           |
| Speed 1 [km/h].             | 40             |
| Load capacity 2 [kg]        | 6000           |
| Speed 2 [km/h].             | 50             |
| Maximum air pressure [bar]. | 3,00           |
| TL/TT                       | TL             |

|                                |            |
|--------------------------------|------------|
| Tyre colour                    | Black      |
| E-Ready                        | No         |
| TRA Code                       | R1-W       |
| Antistatic                     | No         |
| Direction                      | Left       |
| ECE regulation number          | ECE 106    |
| Section width (mm)             | 751        |
| Stat. radius (SLR) [mm]        | 727.00     |
| Speed Radius Index (SRI)       | 775        |
| Rolling circumference [mm].    | 4942.00    |
| Tread depth (mm)               | 56,0       |
| Number of lugs                 | 20x2       |
| Tyre capacity 75% [ltr.]       | 638.25     |
| Assembly Item no. Rim          | • 10000696 |
| Load capacity of rim 1 [kg]    | 7300       |
| Speed Rims 1 [km/h]            | 40         |
| Load capacity of rim 2 [kg]    | 6100       |
| Speed Rims 2 [km/h]            | 50         |
| Maximum speed [km/h].          | 50         |
| Type of drive                  | Towed axle |
| Number of bolt holes           | 12         |
| hub hole diameter [mm].        | 371        |
| Bolt hole circle diameter [mm] | 425        |
| Bolt hole diameter [mm]        | 27.0       |
| Bolt hole design EUWA          | B22 ES 36  |
| Countersinking                 | Sphere     |
| Spherical countersink [mm].    | R18        |

|                          |                |
|--------------------------|----------------|
| Rim material             | steel          |
| RAL                      | RAL7016        |
| Valve seat               | External Valve |
| Disc thickness [mm]      | 15.0           |
| Ventilation holes        | No             |
| Single / multi-part      | einteilig      |
| Hump                     | kein Hump      |
| Valve protection         | VSH            |
| Cavity Sealed            | No             |
| Verschweißung beidseitig | No             |
| Assembly Item no. Valve  | • 47201038     |
| Preassembled valve       | No             |
| TPMS-kompatibles Ventil  | No             |
| Valve hole diameter [mm] | 15.7           |
| Valve design             | Metal valve    |
| Valve designation ETRTO  | V5.01.1        |
| Valve length [mm]        | 50.0           |
| Valve angle [°]          | gerade         |