Bohnenkamp Moving Professionals

Product group	Tyres
Item number	10001234
Valid tyre size	420 / 70 R 24
LI / SI / PR	137 A8 / 134 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax Factor





Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial . tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride • comfort.
- The reduced lug angle allows for reduced rolling . resistance.
- The large contact area ensures smooth running. •
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10001234
EAN	8903094070947
Valid tyre size	420 / 70 R 24
LI / SI / PR	137 A8 / 134 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax Factor
Carcass properties	E-Ready
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	80,80
Recommended rim size	W13
Permitted rim size	W12, W14L
Maximum air pressure [bar].	2,00
Section width (mm)	418
Outer diameter of tyre [mm].	1248
Stat. radius (SLR) [mm]	563
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3696
Tread depth (mm)	43,0
Number of lugs	20x2
E-Ready	Yes

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
137 A8	2300	40		2,00	
134 D	2120	65		2,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.