

## **TYRES**

Product group	Tyres	
Item number	10001753	
Valid tyre size	VF 320 / 90 R 46	
LI / SI / PR	155 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 363 +	



## Notes and features

- The Alliance 363+ is a VF row crop tyre for heavy, selfpropelled field sprayers and tractors.
- It offers up to 40% higher load capacity at the same inflation pressure or the same load capacity at up to 40% reduced inflation pressure compared with a standard tyre.
- The directional tread pattern design, divided in separate blocks, enables good grip on soft surfaces.
- The increased number of lugs and block distribution on the tread pattern ensure good ride comfort and low rolling resistance on roads.
- Its large contact area provides high traction, reduced fuel consumption and low soil compaction.
- The steel belted casing enables uniform ground pressure distribution and protection against damages, thus ensuring a long service life.



## **Technical Informations**

Item number	10001753
EAN	7291050086004
Valid tyre size	VF 320 / 90 R 46
LI / SI / PR	155 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 363 +
TRA Code	R1
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	111,00
Recommended rim size	DW10
Maximum air pressure [bar].	2,80
Section width (mm)	302
Outer diameter of tyre [mm].	1749
Stat. radius (SLR) [mm]	808
Speed Radius Index (SRI)	850
Rolling circumference [mm].	5333
Contact area [cm²]	940.8
Tread depth (mm)	43,0
Number of lugs	35x2
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 D	3875	65		2,80	