

## WHEELS

Product group	Wheels
Item number	10002287
Valid wheel size	600 / 55 - 26.5
Brand	Alliance
Tread pattern	Flotation 328
Valid rim size	AG 20.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	5450
Speed complete wheel [km/h]	50
Nettogewicht [kg] (gültig)	209,91
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15212721
LI / SI / PR	167 B / 163 C, 16 PR
Load capacity 1 [kg]	5450
Speed 1 [km/h].	50
Load capacity 2 [kg]	4875
Speed 2 [km/h].	60
Maximum air pressure [bar].	2,60
TL/TT	TL
Tyre colour	Black

E-Ready	No
Carcass properties	High Speed
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	600
Stat. radius (SLR) [mm]	580
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3850
Tread depth (mm)	25,0
Assembly Item no. Rim	• 33060559
Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	60
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve

Ventilation holes	No
Single / multi-part	einteilig
Hump	H2
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201039
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade