

RIMS

Product group	Rims
Item number	10003036
Valid rim size	W 10 x 48
Rim connection	12/390/430
Offset (mm)	+62
Rim colour	White
Brand	Jantsa



Technical Informations	
Load capacity of rim 1 [kg]	3200
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2700
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	143,00
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	four-part
Rim material	steel

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



RAL	RAL9010
Cavity Sealed	No
Disc thickness [mm]	12
Knurling	without knurling
Verschweißung beidseitig	Yes
Number of additional holes	8
Additional pitch circle diameter [mm].	950
Ventilation holes	No
Number of bolt holes	12
Bolt hole diameter [mm]	16.4
hub hole diameter [mm].	390
Bolt hole circle diameter [mm]	430
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No