

TYRES

Product group	Tyres	
Item number	10003137	
Valid tyre size	140 / 55 - 9 / 4.00 E	
LI / SI / PR	104 A5	
Brand	Maxam	
Tread pattern	MS700	





Notes and features

- The Maxam MS700 is a solid rubber tyre for use on forklift trucks
- Its extra-wide tread enables excellent lifting capacity.
- The tread pattern ensures traction, comfortable handling, good maneuverability and even wear.
- The construction typical of premium tyres with a highquality 3-layer rubber compound (tread, spring and base compound) ensures smooth running and driving comfort.
- Thanks to the EcoPoint3 rubber compound, the tyre is particularly wear-resistant and protected against damage.



Technical Informations

Item number	10003137
EAN	8936096307094
Valid tyre size	140 / 55 - 9 / 4.00 E
LI / SI / PR	104 A5
Brand	Maxam
Tread pattern	MS700
Carcass properties	LIP,Non-Marking,Solid Rubber
Antistatic	No
Tyre colour	Grey
Nettogewicht [kg] (gültig)	10,88
Recommended rim size	4.00E
Section width (mm)	127
Outer diameter of tyre [mm].	378
Stat. radius (SLR) [mm]	189
Rolling circumference [mm].	1188
Tread depth (mm)	27,9
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 A5	900	25	Steering wheel		
	1170	25	Load wheel		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.