

WHEELS

Product group	Wheels
Item number	10003150
Valid wheel size	VF 710 / 50 R 26.5
Brand	Alliance
Tread pattern	Agriflex 389 +
Valid rim size	AG 24.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	65
Nettogewicht [kg] (gültig)	255,04
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15215749
LI / SI / PR	173 D
Load capacity 1 [kg]	6500
Speed 1 [km/h].	65
Maximum air pressure [bar].	2,80
TL/TT	TL
Tyre colour	Black
E-Ready	No
Carcass properties	Steel Belted

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	732
Stat. radius (SLR) [mm]	602
Rolling circumference [mm].	4271
Tread depth (mm)	26,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	469
Assembly Item no. Rim	• 33060572
Load capacity of rim 1 [kg]	10650
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7850
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No

Single / multi-part	einteilig
Hump	H2
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201037
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1.short
Valve length [mm]	41.5
Valve angle [°]	gerade