# Bohnenkamp Moving Professionals

10.05.2025

#### TYRES

| Product group   | Tyres              |
|-----------------|--------------------|
| Item number     | 10003231           |
| Valid tyre size | 28 x 9 - 15 / 7.00 |
| LI / SI / PR    | 165 A5             |
| Brand           | Maxam              |
| Tread pattern   | MS700              |



#### Notes and features

- The Maxam MS700 is a solid rubber tyre for use on forklift trucks.
- Its extra-wide tread enables excellent lifting capacity.
- The tread pattern ensures traction, comfortable handling, good maneuverability and even wear.
- The construction typical of premium tyres with a highquality 3-layer rubber compound (tread, spring and base compound) ensures smooth running and driving comfort.
- Thanks to the EcoPoint3 rubber compound, the tyre is particularly wear-resistant and protected against damage.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

| Item number                  | 10003231           |
|------------------------------|--------------------|
| EAN                          | 8936096306677      |
| Valid tyre size              | 28 x 9 - 15 / 7.00 |
| Alternative size 1           | 225/75-15          |
| LI / SI / PR                 | 165 A5             |
| Brand                        | Maxam              |
| Tread pattern                | MS700              |
| Carcass properties           | LIP,Solid Rubber   |
| Antistatic                   | No                 |
| Tyre colour                  | Black              |
| Nettogewicht [kg] (gültig)   | 62,45              |
| Recommended rim size         | 7.00               |
| Section width (mm)           | 215                |
| Outer diameter of tyre [mm]. | 693                |
| Stat. radius (SLR) [mm]      | 347                |
| Rolling circumference [mm].  | 2177               |
| Tread depth (mm)             | 50,0               |
| E-Ready                      | No                 |

### Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position  | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|----------------|-----------------------------|--------------|
| 146 A5 | 3000               | 25           | Steering wheel |                             |              |
|        | 3900               | 25           | Load wheel     |                             |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.