

TYRES

Product group	Tyres	
Item number	10003279	
Valid tyre size	6.50 - 10 / 5.00 F	
LI / SI / PR	128 A5	
Brand	Maxam	
Tread pattern	MS700	





Notes and features

- The Maxam MS700 is a solid rubber tyre for use on forklift trucks
- Its extra-wide tread enables excellent lifting capacity.
- The tread pattern ensures traction, comfortable handling, good maneuverability and even wear.
- The construction typical of premium tyres with a highquality 3-layer rubber compound (tread, spring and base compound) ensures smooth running and driving comfort.
- Thanks to the EcoPoint3 rubber compound, the tyre is particularly wear-resistant and protected against damage.



Technical Informations

Item number	10003279
EAN	8936096306370
Valid tyre size	6.50 - 10 / 5.00 F
LI / SI / PR	128 A5
Brand	Maxam
Tread pattern	MS700
Carcass properties	STD,Solid Rubber
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	36,78
Recommended rim size	5.00F
Section width (mm)	165
Outer diameter of tyre [mm].	572
Stat. radius (SLR) [mm]	286
Rolling circumference [mm].	1796
Tread depth (mm)	51,0
E-Ready	No

Load capacity

	Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
:	128 A5	1800	25	Steering wheel		
		2340	25	Load wheel		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.