

TYRES

Product group	Tyres	
Item number	10004365	
Valid tyre size	VF 650 / 75 R 42 NRO	
LI / SI / PR	180 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	TRAXION OPTIMALL	





Notes and features

- The Vredestein Traxion Optimall is an innovative VF tyre for high-performance tractors.
- Its extremely flexible casing design enables a reduction of the inflation pressure by up to 25% for low soil compaction.
- The upper bead zone is specially reinforced and provides good stability, even at low inflation pressure.
- The strong lug end in the tread centre provides stability, low wear and good self-cleaning properties.
- In on-road use, the tread with a high rubber content ensures slow wear and a long service life.
- The rounded tread contour enables good ride comfort.



Technical Informations

Item number	10004365
EAN	8714692999772
Valid tyre size	VF 650 / 75 R 42 NRO
LI / SI / PR	180 D
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION OPTIMALL
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	338,50
Recommended rim size	DW23B
Permitted rim size	DW21B
Maximum air pressure [bar].	2,00
Section width (mm)	675
Outer diameter of tyre [mm].	2055
Stat. radius (SLR) [mm]	885
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6075
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180 D	8000	65		2,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.