

TYRES

Product group	Tyres	
Item number	10004450	
Valid tyre size	1050 / 50 R 32	
LI / SI / PR	182 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Multistar 376	





Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning properties.
- Nylon casing with reinforced steel belt.
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.



Technical Informations

Item number	10004450
EAN	8903635058809
Valid tyre size	1050 / 50 R 32
LI / SI / PR	182 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	387,30
Recommended rim size	36.00VA
Maximum air pressure [bar].	3,00
Section width (mm)	1050
Outer diameter of tyre [mm].	1870
Stat. radius (SLR) [mm]	806
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5672
Contact area [cm²]	4987
Tread depth (mm)	42,5
Number of lugs	20x2
Tyre capacity 75% [Itr.]	1244.93
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Ind	ex	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182	2 D	8500	65		3,00	