

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 10004451 |
| Valid tyre size | 650 / 65 R 38 |
| LI / SI / PR | 169 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Forestar 668 III |



Technical Informations

| | |
|--------------------|------------------|
| Item number | 10004451 |
| EAN | 8903635056966 |
| Valid tyre size | 650 / 65 R 38 |
| LI / SI / PR | 169 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Forestar 668 III |
| TRA Code | R1-W |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |

| | |
|------------------------------|---------|
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 298,00 |
| Recommended rim size | DW20B |
| Permitted rim size | TW20B |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 645 |
| Outer diameter of tyre [mm]. | 1811 |
| Stat. radius (SLR) [mm] | 840 |
| Speed Radius Index (SRI) | 850 |
| Rolling circumference [mm]. | 5410 |
| Contact area [cm²] | 2080 |
| Tread depth (mm) | 53,0 |
| Number of lugs | 19x2 |
| Tyre capacity 75% [ltr.] | 581.25 |
| Guarantee period | 5 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 169 D | 5800 | 65 | | 3,20 | |