Bohnenkamp Moving Professionals

09.05.2025

TYRES

Product group	Tyres	
Item number	10004482	
Valid tyre size	VF 270 / 95 R 32	
LI / SI / PR	138 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 363 + XT	





Notes and features

- The Alliance Agriflex 363 + XT is a VF row crop tyre for tractors, self-propelled sprayers and similar vehicles.
- Its directional tread pattern enables efficient use in the field and on the road.
- The blocks arranged in the middle of the tread ensure reduced vibration and good rolling behavior on the road.
- The tread blocks are arranged on the outside of the tread to form lugs and guarantee optimum traction in the field.
- The Agriflex + technology enables up to 40% higher load capacities compared to a standard tyre with the same air pressure.
- The carcass is very well protected against premature wear by a stubble guard and a particularly wear-resistant rubber compound.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10004482
EAN	8903635057666
Valid tyre size	VF 270 / 95 R 32
LI / SI / PR	138 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 363 + XT
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	63,60
Recommended rim size	W9
Maximum air pressure [bar].	2,40
Section width (mm)	270
Outer diameter of tyre [mm].	1326
Stat. radius (SLR) [mm]	609
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3925
Contact area [cm²]	627.744
Tread depth (mm)	35,0
Number of lugs	29x2
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 D	2360	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.