

TYRES

Product group	Tyres	
Item number	10004494	
Valid tyre size	405 / 70 R 18	
LI / SI / PR	153 A2 / 141 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Multiuse 550	



Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.



Technical Informations

Item number	10004494
EAN	8903635031321
Valid tyre size	405 / 70 R 18
Alternative size 1	16.0 / 70 R 18
LI / SI / PR	153 A2 / 141 B
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	61,70
Recommended rim size	13
Maximum air pressure [bar].	3,75
Section width (mm)	404
Outer diameter of tyre [mm].	1021
Stat. radius (SLR) [mm]	468
Speed Radius Index (SRI)	475
Rolling circumference [mm].	3059
Contact area [cm²]	1011.2
Tread depth (mm)	26,8
Number of lugs	18x2
Tyre capacity 75% [ltr.]	131.1

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A2	3650	10		3,75	
141 B	2575	50		3,75	