

TYRES

Product group	Tyres
Item number	10004495
Valid tyre size	445 / 70 R 22.5
LI / SI / PR	182 A2 / 175 A8
TL/TT	TL
Brand	Alliance
Tread pattern	624



Notes and features

- The Alliance 624 All Steel is characterised by low rolling resistance, high load capacity as well as a long service life.
- The tyre has good self-cleaning properties for best protection to limit damage during intensive applications.
- The solid centre blocks are best suited for use on the road and provide enhanced stability.
- The reinforced shoulder area provides increased puncture protection.
- Most suitable for use with mobile excavators and similar vehicles.

Technical Informations

Item number	10004495
EAN	8903635046998
Valid tyre size	445 / 70 R 22.5
Alternative size 1	18 R 22.5
LI / SI / PR	182 A2 / 175 A8
TL/TT	TL
Brand	Alliance
Tread pattern	624
TRA Code	R4
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	126,50
Recommended rim size	14.00
Maximum air pressure [bar].	7,50
Section width (mm)	454
Outer diameter of tyre [mm].	1195
Stat. radius (SLR) [mm]	539
Rolling circumference [mm].	3646
Tread depth (mm)	26,5
Number of lugs	17x2
Tyre capacity 75% [litr.]	121.5
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182 A2	8500	10		7,50	
175 A8	6900	40		7,50	