

TYRES

Product group	Tyres	
Item number	10004496	
Valid tyre size	300 / 95 R 52	
LI / SI / PR	152 A8 / 149 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	350	



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



Technical Informations

Item number	10004496
EAN	8903635012351
Valid tyre size	300 / 95 R 52
LI / SI / PR	152 A8 / 149 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	93,30
Recommended rim size	W9
Permitted rim size	W10, DW10, W11, DW11
Maximum air pressure [bar].	3,60
Section width (mm)	310
Outer diameter of tyre [mm].	1890
Stat. radius (SLR) [mm]	898
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5797
Contact area [cm²]	861.7
Tread depth (mm)	38,0
Number of lugs	30x2
Tyre capacity 75% [ltr.]	182.6
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		3,60	
149 D	3250	65		3,60	