

TYRES

Product group	Tyres
Item number	10004503
Valid tyre size	230 / 95 R 40
LI / SI / PR	135 A8 / 132 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	10004503
EAN	8903635020172
Valid tyre size	230 / 95 R 40
Alternative size 1	9.5 R 40
LI / SI / PR	135 A8 / 132 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	54,00
Recommended rim size	W7
Permitted rim size	W8
Maximum air pressure [bar].	3,60
Section width (mm)	241
Outer diameter of tyre [mm].	1460
Stat. radius (SLR) [mm]	692
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4471
Contact area [cm ²]	487.7
Tread depth (mm)	35,0
Number of lugs	27x2
Tyre capacity 75% [ltr.]	86.7
Guarantee period	7 years

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 A8	2180	40		3,60	
132 D	2000	65		3,60	