

TYRES

Product group	Tyres
Item number	10004560
Valid tyre size	320 / 90 R 50
LI / SI / PR	153 A8 / 150 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	10004560
EAN	8903635031390
Valid tyre size	320 / 90 R 50
Alternative size 1	12.4 R 50
LI / SI / PR	153 A8 / 150 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	99,40
Recommended rim size	W10
Permitted rim size	W9, W11
Maximum air pressure [bar].	3,60
Section width (mm)	325
Outer diameter of tyre [mm].	1867
Stat. radius (SLR) [mm]	872
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5684
Contact area [cm²]	948.1
Tread depth (mm)	41,0
Number of lugs	32x2
Tyre capacity 75% [ltr.]	198.08
Guarantee period	7 years

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40		3,60	
150 D	3350	65		3,60	