

TYRES

Product group	Tyres	
Item number	10004615	
Valid tyre size	600 / 50 - 22.5	
LI / SI / PR	158 D / 157 E, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotation 328	



≈ALLIANCE

Notes and features

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.

• Also for tractors (turf rolls).



Technical Informations

Item number	10004615
EAN	8903635056997
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	158 D / 157 E, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
TRA Code	13
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	102,20
Recommended rim size	AG20.00
Maximum air pressure [bar].	2,60
Section width (mm)	600
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	551
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3450
Contact area [cm²]	1686.2
Tread depth (mm)	26,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	236.1
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		2,60	
157 E	4125	70		2,60	