

TYRES

Product group	Tyres
Item number	10004667
Valid tyre size	560 / 45 R 22.5
LI / SI / PR	156 D
TL/TT	TL
Brand	Alliance
Tread pattern	380



 **ALLIANCE**

Notes and features

- Flotation radial tyres with steel belt reinforcement for off-road transport work.
- Very good self-cleaning due to wide tread pattern spaces.
- Large air volume enables high load capacities even with low inflation pressures for use that is gentle on the soil.
- Its special non-directional tread pattern enables very good self-cleaning and uniform traction in the field.
- The tyre is only suitable for short transport journeys on the road.
- Ideal for manure spreaders, slurry tankers and vehicles used on construction sites.

Technical Informations

Item number	10004667
EAN	8903635069966
Valid tyre size	560 / 45 R 22.5
LI / SI / PR	156 D
TL/TT	TL
Brand	Alliance
Tread pattern	380
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	96,10
Recommended rim size	AG16.00
Maximum air pressure [bar].	5,00
Section width (mm)	554
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	488
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3324
Contact area [cm²]	1178
Tread depth (mm)	25,0
Number of lugs	16x2
Tyre capacity 75% [ltr.]	223.5
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 D	4000	65		5,00	