

TYRES

Product group	Tyres
Item number	10004723
Valid tyre size	1000 / 50 R 25
LI / SI / PR	172 A8 / 166 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.

Technical Informations

Item number	10004723
EAN	8903635058816
Valid tyre size	1000 / 50 R 25
LI / SI / PR	172 A8 / 166 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375
TRA Code	R1
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	385,70
Recommended rim size	36.0TH
Maximum air pressure [bar].	2,40
Section width (mm)	1065
Outer diameter of tyre [mm].	1660
Stat. radius (SLR) [mm]	772
Speed Radius Index (SRI)	775
Rolling circumference [mm].	5159
Contact area [cm²]	3214.6
Tread depth (mm)	52,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	1053.6
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		2,40	
166 D	5300	65		2,40	