

TYRES

Product group	Tyres	
Item number	10004810	
Valid tyre size	VF 710 / 70 R 38 CFO 181 D TL	
LI / SI / PR		
TL/TT		
Brand	Alliance	
Tread pattern	Agriflex 372 +	



Notes and features

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.



Technical Informations

Item number	10004810		
EAN	8903635058731		
Valid tyre size	VF 710 / 70 R 38 CFO		
LI / SI / PR	181 D		
TL/TT	TL		
Brand	Alliance		
Tread pattern	Agriflex 372 +		
TRA Code	R1-W		
Carcass properties	Steel Belted		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 106		
Nettogewicht [kg] (gültig)	303,10		
Recommended rim size	DW25B		
Permitted rim size	DW23B, DW24B		
Maximum air pressure [bar].	2,00		
Section width (mm)	720		
Outer diameter of tyre [mm].	1959		
Stat. radius (SLR) [mm]	854		
Speed Radius Index (SRI)	925		
Rolling circumference [mm].	5766		
Contact area [cm²]	4335.9		
Tread depth (mm)	61,0		
Number of lugs	19x2		
Tyre capacity 75% [ltr.]	832.95		
Guarantee period	10 years		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 D	8250	65		2,00	