Bohnenkamp 📕 🛑 Moving Professionals

TYRES

Product group	Tyres
Item number	10004812
Valid tyre size	520 / 85 R 46
LI / SI / PR	173 A8 / 169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agri Star II



Notes and features

- The Alliance Agri Star II is a new, modern agricultural . tractor tyre with speed index "D" (up to 65 km/h) for tractors in all corresponding power ranges.
- The special Stratified Layer Technology provides very . good traction and ride comfort in the field and on the road.
- Stratified Layer Technology combines 2 layers of . agricultural lugs so that after initial wear of the external lugs, the lower layer of lugs continue to provide traction.
- Even after 40% wear, the 2nd lug layer guarantees good . grip and effective traction and thus a long service life.
- The wide contact area ensures low soil compaction.
- The special abrasion- and puncture-resistant rubber compound (Stubble Guard) protects the tyre from damage caused by grain stubble.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10004812
EAN	8903635070085
Valid tyre size	520 / 85 R 46
LI / SI / PR	173 A8 / 169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agri Star II
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	235,80
Recommended rim size	DW16L
Permitted rim size	W16L, W15L, W15, W18L, DW18L
Maximum air pressure [bar].	3,20
Section width (mm)	526
Outer diameter of tyre [mm].	2050
Stat. radius (SLR) [mm]	956
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6187
Contact area [cm²]	2197.3
Tread depth (mm)	55,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	585.75
Guarantee period	10 years

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

10.05.2025

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	40		3,20	
169 D	5800	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.