

TYRES

Product group	Tyres
Item number	10004814
Valid tyre size	500 / 70 R 24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550



Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.

Technical Informations

Item number	10004814
EAN	8903635059042
Valid tyre size	500 / 70 R 24
Alternative size 1	19.5 LR 24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	108,20
Recommended rim size	DW16L
Permitted rim size	DW15L
Maximum air pressure [bar].	4,00
Section width (mm)	504
Outer diameter of tyre [mm].	1303
Stat. radius (SLR) [mm]	590
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3917
Contact area [cm²]	1545
Tread depth (mm)	28,8
Number of lugs	21x2
Tyre capacity 75% [ltr.]	282.75

Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	
164 B	5000	50		4,00	