

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 10004882       |
| Valid tyre size | 380 / 90 R 50  |
| LI / SI / PR    | 154 A8 / 151 D |
| TL/TT           | TL             |
| Brand           | Alliance       |
| Tread pattern   | 350            |



Bohnenkamp  
■ ■ ● Moving Professionals

 **ALLIANCE**

## Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 10004882       |
| EAN                          | 8903635059172  |
| Valid tyre size              | 380 / 90 R 50  |
| Alternative size 1           | 14.9R50        |
| LI / SI / PR                 | 154 A8 / 151 D |
| TL/TT                        | TL             |
| Brand                        | Alliance       |
| Tread pattern                | 350            |
| TRA Code                     | R1-W           |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 135,00         |
| Recommended rim size         | W12            |
| Permitted rim size           | W13            |
| Maximum air pressure [bar].  | 2,40           |
| Section width (mm)           | 384            |
| Outer diameter of tyre [mm]. | 1950           |
| Stat. radius (SLR) [mm]      | 908            |
| Speed Radius Index (SRI)     | 975            |
| Rolling circumference [mm].  | 5961           |
| Contact area [cm²]           | 1278.6         |
| Tread depth (mm)             | 47,0           |
| Number of lugs               | 30x2           |
| Tyre capacity 75% [ltr.]     | 332.78         |
| Guarantee period             | 7 years        |

|         |    |
|---------|----|
| E-Ready | No |
|---------|----|

Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 154 A8 | 3450               | 40           |               | 2,40                     |              |
| 151 D  | 3750               | 65           |               | 2,40                     |              |