

TYRES

|                 |               |
|-----------------|---------------|
| Product group   | Tyres         |
| Item number     | 10626106      |
| Valid tyre size | 250 / 85 R 24 |
| LI / SI / PR    | 109 D / 106 E |
| TL/TT           | TL            |
| Brand           | Firestone     |
| Tread pattern   | Performer 85  |



Notes and features

- Narrow tyre for maintenance of row crops.
  - High load capacity.
  - Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
  - Long service life.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 10626106      |
| EAN                          | 3286340562119 |
| Valid tyre size              | 250 / 85 R 24 |
| Alternative size 1           | 9.5R24        |
| LI / SI / PR                 | 109 D / 106 E |
| TL/TT                        | TL            |
| Brand                        | Firestone     |
| Tread pattern                | Performer 85  |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | not necessary |
| Nettogewicht [kg] (gültig)   | 36,95         |
| Recommended rim size         | 8             |
| Permitted rim size           | 7             |
| Maximum air pressure [bar].  | 1,60          |
| Section width (mm)           | 245           |
| Outer diameter of tyre [mm]. | 1038          |
| Stat. radius (SLR) [mm]      | 465           |
| Rolling circumference [mm].  | 3114          |
| Tread depth (mm)             | 37,0          |
| Number of lugs               | 20x2          |
| Tyre capacity 75% [ltr.]     | 61.5          |
| Guarantee period             | 10 years      |
| E-Ready                      | No            |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 109 D | 1030               | 65           |               | 1,60                     |              |
| 106 E | 950                | 70           |               | 1,60                     |              |