

TYRES

Product group	Tyres
Item number	10627315
Valid tyre size	320 / 85 R 34
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Firestone
Tread pattern	R9000



Notes and features

- Narrow tyre for maintenance applications and field spraying.
- Optimum traction in all conditions.
 - Even tread wear, durable.

Technical Informations

Item number	10627315
EAN	3286345427611
Valid tyre size	320 / 85 R 34
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Firestone
Tread pattern	R9000
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	85,00
Recommended rim size	10
Maximum air pressure [bar].	2,40
Section width (mm)	315
Outer diameter of tyre [mm].	1408
Stat. radius (SLR) [mm]	653
Rolling circumference [mm].	4240
Tread depth (mm)	41,0
Number of lugs	26x2
Tyre capacity 75% [ltr.]	148.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		2,40	
133 B	2060	50		2,40	