

TYRES

Product group	Tyres
Item number	10926210
Valid tyre size	750 / 65 R 26
LI / SI / PR	169 A8 / 166 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
  - Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

## Technical Informations

Item number	10926210
EAN	8059971067149
Valid tyre size	750 / 65 R 26
LI / SI / PR	169 A8 / 166 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	238,70
Recommended rim size	25
Permitted rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	738
Outer diameter of tyre [mm].	1620
Stat. radius (SLR) [mm]	720
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4800
Tread depth (mm)	56,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A8	5800	40		2,40	
166 D	5300	65		2,40	