

TYRES

Product group	Tyres
Item number	10926462
Valid tyre size	710 / 60 R 34
LI / SI / PR	167 A8 / 164 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10926462
EAN	8059971068931
Valid tyre size	710 / 60 R 34
LI / SI / PR	167 A8 / 164 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	234,00
Recommended rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	700
Outer diameter of tyre [mm].	1700
Stat. radius (SLR) [mm]	770
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5060
Tread depth (mm)	60,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		2,40	
164 D	5000	65		2,40	