

TYRES

Product group	Tyres
Item number	10927922
Valid tyre size	620 / 70 R 30
LI / SI / PR	178 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
 - Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10927922
EAN	8059971043792
Valid tyre size	620 / 70 R 30
LI / SI / PR	178 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	204,50
Recommended rim size	18
Permitted rim size	20, 21
Maximum air pressure [bar].	2,40
Section width (mm)	625
Outer diameter of tyre [mm].	1595
Stat. radius (SLR) [mm]	680
Rolling circumference [mm].	4770
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40	Free Rolling	2,40	
166 A8	5300	40	Drive Wheel	2,40	