

TYRES

Product group	Tyres
Item number	10928085
Valid tyre size	650 / 75 R 38
LI / SI / PR	172 A8 / 169 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
 - Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10928085
EAN	8059971060478
Valid tyre size	650 / 75 R 38
LI / SI / PR	172 A8 / 169 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	265,00
Recommended rim size	20
Permitted rim size	21, 23
Maximum air pressure [bar].	2,40
Section width (mm)	657
Outer diameter of tyre [mm].	1944
Stat. radius (SLR) [mm]	872
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5795
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		2,40	
169 D	5800	65		2,40	