

TYRES

Product group	Tyres
Item number	10928106
Valid tyre size	900 / 60 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
  - Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

## Technical Informations

Item number	10928106
EAN	8059971057027
Valid tyre size	900 / 60 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	401,80
Recommended rim size	27
Permitted rim size	30
Maximum air pressure [bar].	2,40
Section width (mm)	870
Outer diameter of tyre [mm].	2060
Stat. radius (SLR) [mm]	918
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6115
Tread depth (mm)	63,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		2,40	
178 D	7500	65		2,40	