

TYRES

Product group	Tyres
Item number	12426785
Valid tyre size	230 / 95 R 40
LI / SI / PR	135 A8 / 132 D
TL/TT	TL
Brand	Kleber
Tread pattern	Cropker





Notes and features

- The Kleber Cropker is a premium crop tyre for tractors in the 80-200 hp performance range.
- Compared with its predecessor, the Kleber Super 3, the Cropker offers a higher load capacity and the double identifier D/A8.
- It can be used as a FRT (Free Rolling Tyre) on towed vehicles with with a load surcharge of up to 20% at 40 km/h.
- Thanks to the special root-friendly lug shoulders, plants in row crops are optimally protected.
- Its tread pattern reinforced in the centre of the tread provides improved driving and steering precision and longer mileage.
- Due to the shape of the lugs and the spaces between them, the tyre offers very good self-cleaning properties.



Technical Informations

Item number	12426785
EAN	3528702657843
Valid tyre size	230 / 95 R 40
Alternative size 1	9.5R40
LI / SI / PR	135 A8 / 132 D
TL/TT	TL
Brand	Kleber
Tread pattern	Cropker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	51,00
Recommended rim size	7
Permitted rim size	8
Maximum air pressure [bar].	4,00
Section width (mm)	225
Outer diameter of tyre [mm].	1448
Stat. radius (SLR) [mm]	684
Rolling circumference [mm].	4350
Tread depth (mm)	36,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	92
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 A8	2180	40		4,00	
132 D	2000	65		4,00	