

TYRES

| Product group | Tyres | |
|-----------------|---------------|--|
| Item number | 12500161 | |
| Valid tyre size | 13 x 5.00 - 6 | |
| LI / SI / PR | 52 A4, 4 PR | |
| TL/TT | TL | |
| Brand | Carlisle | |
| Tread pattern | Smooth | |





Notes and features

- The Carlisle Smooth is a tyre for transport vehicles, rideon mowers, garden tractors and wheelbarrows.
- The smooth tread pattern with rounded shoulders protects the soil and does not leave any traces on the ground.
- Thanks to the special rubber compound, the tyre is very durable



Technical Informations

| Item number | 12500161 |
|------------------------------|---------------|
| EAN | 5999110827766 |
| Valid tyre size | 13 x 5.00 - 6 |
| Alternative size 1 | 130/70-6 |
| LI / SI / PR | 52 A4, 4 PR |
| TL/TT | TL |
| Brand | Carlisle |
| Tread pattern | Smooth |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 1,90 |
| Recommended rim size | 3.50 |
| Maximum air pressure [bar]. | 2,75 |
| Section width (mm) | 122 |
| Outer diameter of tyre [mm]. | 323 |
| Stat. radius (SLR) [mm] | 143 |
| Rolling circumference [mm]. | 956 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 52 A4 | 200 | 20 | | 2,75 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.