

TYRES

Product group	Tyres
Item number	13327390
Valid tyre size	500 / 70 R 24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL



Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.
 - Reinforced sidewalls.
- Solid lugs.
 - Belt plies made from steel mesh.

Technical Informations

Item number	13327390
EAN	3528705427948
Valid tyre size	500 / 70 R 24
Alternative size 1	19.5R24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	114,00
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	4,00
Section width (mm)	511
Outer diameter of tyre [mm].	1302
Stat. radius (SLR) [mm]	583
Rolling circumference [mm].	3866
Tread depth (mm)	36,0
Number of lugs	18x2
Lug width (mm)	46
Tyre capacity 75% [ltr.]	266
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	
164 B	5000	50		4,00	