TYRES

Product group	Tyres
Item number	13327422
Valid tyre size	480 / 80 R 26
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL

MICHELIN

Notes and features

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers.

- Reinforced sidewalls.

- Solid lugs.

- Belt plies made from steel mesh.

Bohnenkamp
Moving Professionals

10.05.2025

Technical Informations

Item number	13327422
EAN	3528704259793
Valid tyre size	480 / 80 R 26
Alternative size 1	18.4R26
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	Michelin
Tread pattern	XMCL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	132,00
Recommended rim size	15
Permitted rim size	16
Maximum air pressure [bar].	4,00
Section width (mm)	495
Outer diameter of tyre [mm].	1422
Stat. radius (SLR) [mm]	635
Rolling circumference [mm].	4218
Tread depth (mm)	36,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	302
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		4,00	
167 B	5450	50		4,00	