Bohnenkamp Moving Professionals

11.05.2025

TYRES

Product group	Tyres
Item number	13375022
Valid tyre size	445 / 70 R 22.5
LI / SI / PR	182 A2 / 175 A8
TL/TT	TL
Brand	Michelin
Tread pattern	XF





Notes and features

- Wide-base tyre for mobile excavators.
- Best traction properties.

• Excellent resistance.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	13375022
EAN	3528700735222
Valid tyre size	445 / 70 R 22.5
LI / SI / PR	182 A2 / 175 A8
TL/TT	TL
Brand	Michelin
Tread pattern	XF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	120,00
Recommended rim size	14.00
Maximum air pressure [bar].	7,50
Section width (mm)	452
Outer diameter of tyre [mm].	1192
Stat. radius (SLR) [mm]	539
Rolling circumference [mm].	3582
Tread depth (mm)	20,0
Number of lugs	17x2
Tyre capacity 75% [ltr.]	191
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182 A2	8500	10		7,50	
175 A8	6900	40		7,50	

11.05.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.