

## **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 13375340       |
| Valid tyre size | 500 / 70 R 24  |
| LI / SI / PR    | 164 A8 / 159 D |
| TL/TT           | TL             |
| Brand           | Michelin       |
| Tread pattern   | CrossGrip      |





## Notes and features

- The Michelin CrossGrip is a versatile municipal tyre for all-season use on roads, grass and snow.
- The tyre provides high loading capacities at speeds up to 65 km/h.
- Its special tread pattern design enables very good traction, even in wintry weather conditions.
- The tyre features excellent steering characteristics, also in reverse.



## **Technical Informations**

| Item number                  | 13375340       |
|------------------------------|----------------|
| EAN                          | 3528708752702  |
| Valid tyre size              | 500 / 70 R 24  |
| LI / SI / PR                 | 164 A8 / 159 D |
| TL/TT                        | TL             |
| Brand                        | Michelin       |
| Tread pattern                | CrossGrip      |
| M+S                          | M+S            |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | not necessary  |
| Nettogewicht [kg] (gültig)   | 104,00         |
| Recommended rim size         | DW16A          |
| Permitted rim size           | DW15L, TW16L   |
| Maximum air pressure [bar].  | 4,00           |
| Section width (mm)           | 513            |
| Outer diameter of tyre [mm]. | 1292           |
| Stat. radius (SLR) [mm]      | 580            |
| Rolling circumference [mm].  | 3998           |
| Tread depth (mm)             | 28,0           |
| Number of lugs               | 36x2           |
| Tyre capacity 75% [ltr.]     | 265.5          |
| E-Ready                      | No             |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 164 A8 | 5000               | 40           |               | 4,00                        |              |
| 159 D  | 4375               | 65           |               | 4,00                        |              |