Bohnenkamp Moving Professionals

10.05.2025

TYRES

| Product group | Tyres |
|-----------------|----------------------|
| Item number | 13626403 |
| Valid tyre size | IF 800 / 70 R 32 CFO |
| LI / SI / PR | 182 A8 |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM3000 |



Notes and features

- Radial tractor tyre featuring IF technology and Trelleborg's BLUE TYRE technology for state-of-the-art harvesters.
- 20% higher load capacity at constant inflation pressure or 20% lower inflation pressure with the same payload compared with standard tyres.
- Suitable for cyclic field operation (CFO = Cyclic Field Operation).
- New tread pattern design and further improved casing maximise load capacity and soil protection.
- Increases harvest productivity.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 13626403 |
|------------------------------|----------------------|
| EAN | 8059971015362 |
| Valid tyre size | IF 800 / 70 R 32 CFO |
| LI / SI / PR | 182 A8 |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM3000 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 341,00 |
| Recommended rim size | 27 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 775 |
| Outer diameter of tyre [mm]. | 1950 |
| Stat. radius (SLR) [mm] | 850 |
| Rolling circumference [mm]. | 5845 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 182 A8 | 8500 | 40 | | 2,40 | |