

## **TYRES**

| Product group   | Tyres         |
|-----------------|---------------|
| Item number     | 14826075      |
| Valid tyre size | 650 / 75 R 38 |
| LI / SI / PR    | 169 D         |
| TL/TT           | TL            |
| Brand           | Vredestein    |
| Tread pattern   | TRAXION XXL   |





## Notes and features

- The Traxion XXL was developed for tractors with an engine performance above 160 hp.
- Its special tread pattern and flexible casing provide a large contact area and thus even ground pressure distribution.
- The large tyre volume enables a high load capacity at low inflation pressure.
- In field applications, the tyre offers excellent traction.
- In transport journeys, it distinguishes itself through high ride comfort and safety at speeds up to 70 km/h.



## **Technical Informations**

| Item number                  | 14826075      |
|------------------------------|---------------|
| EAN                          | 8714692206269 |
| Valid tyre size              | 650 / 75 R 38 |
| LI / SI / PR                 | 169 D         |
| TL/TT                        | TL            |
| Brand                        | Vredestein    |
| Tread pattern                | TRAXION XXL   |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 106       |
| Nettogewicht [kg] (gültig)   | 288,59        |
| Recommended rim size         | 23            |
| Permitted rim size           | 20, 21        |
| Maximum air pressure [bar].  | 2,40          |
| Section width (mm)           | 695           |
| Outer diameter of tyre [mm]. | 1935          |
| Stat. radius (SLR) [mm]      | 890           |
| Rolling circumference [mm].  | 5775          |
| Tread depth (mm)             | 54,0          |
| Tyre capacity 75% [ltr.]     | 705           |
| E-Ready                      | No            |

## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 169 D | 5800               | 65           |               | 2,40                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.