

TYRES

Product group	Tyres
Item number	15212550
Valid tyre size	20.00 - 20
LI / SI / PR	169 A8 / 165 B, 20 PR
TL/TT	TT
Brand	Alliance
Tread pattern	222



Notes and features

- The Alliance 222 is an implement tyre for agricultural trailers and towed machines.
- The high-volume tyre with extra wide contact area offers high loading capacity and optimum soil protection at the same time.
- It is ideally suitable for field applications and road transport.

Technical Informations

Item number	15212550
EAN	7291050000062
Valid tyre size	20.00 - 20
LI / SI / PR	169 A8 / 165 B, 20 PR
TL/TT	TT
Brand	Alliance
Tread pattern	222
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	88,23
Recommended rim size	16
Permitted rim size	20SDC
Maximum air pressure [bar].	3,90
Section width (mm)	498
Outer diameter of tyre [mm].	1400
Stat. radius (SLR) [mm]	598
Rolling circumference [mm].	3991
Tread depth (mm)	12,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A8	5800	30	Free Rolling	3,90	
165 B	5150	40	Free Rolling	3,90	