

TYRES

Product group	Tyres	
Item number	15212635	
Valid tyre size	600 / 55 - 22.5	
LI / SI / PR	156 A8 / 169 A8, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotation 331	





Notes and features

- The Alliance 331 is perfectly suited to on- and off-road agricultural applications e.g. for tractors, agricultural trailers and similar vehicles.
- Its main characteristics are a high load capacity and low inflation pressure.
- It replaces conventional tractor tyres or dual constructions because of its high traction, high load capacity and at the same time protects the soil.
- Thanks to the permitted speed of 50 km/h, it can also be used on off-road trucks and trailers.
- The strong nylon construction and special rubber compound make the tyre very durable.



Technical Informations

Item number	15212635
EAN	7291050041638
Valid tyre size	600 / 55 - 22.5
LI / SI / PR	156 A8 / 169 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 331
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	130,13
Recommended rim size	20.00
Maximum air pressure [bar].	2,60
Section width (mm)	602
Outer diameter of tyre [mm].	1270
Stat. radius (SLR) [mm]	533
Rolling circumference [mm].	3580
Tread depth (mm)	39,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40	Drive Wheel	2,60	
169 A8	5800	40	Free Rolling	2,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.