

TYRES

| | |
|-----------------|----------------------|
| Product group | Tyres |
| Item number | 15212638 |
| Valid tyre size | 600 / 50 - 22.5 |
| LI / SI / PR | 158 D / 157 E, 16 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Flotation 328 |



Notes and features

- Bias flotation tyre for towed vehicles.
- Also for tractors (turf rolls).
- Soil-protecting tread pattern.

Technical Informations

| | |
|------------------------------|----------------------|
| Item number | 15212638 |
| EAN | 7291050005296 |
| Valid tyre size | 600 / 50 - 22.5 |
| LI / SI / PR | 158 D / 157 E, 16 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Flotation 328 |
| Carcass properties | High Speed |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 99,13 |
| Recommended rim size | 20.00 |
| Maximum air pressure [bar]. | 2,60 |
| Section width (mm) | 600 |
| Outer diameter of tyre [mm]. | 1170 |
| Stat. radius (SLR) [mm] | 520 |
| Rolling circumference [mm]. | 3450 |
| Tread depth (mm) | 25,0 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 158 D | 4250 | 65 | | 2,60 | |
| 157 E | 4125 | 70 | | 2,60 | |