

TYRES

| Product group | Tyres | |
|-----------------|-----------------------|--|
| Item number | 15212674 | |
| Valid tyre size | 800 / 35 - 22.5 | |
| LI / SI / PR | 169 A8 / 162 D, 16 PR | |
| TL/TT | TL | |
| Brand | Alliance | |
| Tread pattern | 128 | |





Notes and features

- The Alliance 128 was designed for agricultural trailers in the field and on the road.
- The special tread pattern with shoulder lugs provides high traction in the field.
- The grooved tread pattern in the middle of the tread provides comfortable driving performance on roads during transport journeys.
- The tyre enables high loading capacity at low inflation pressure, optimum soil protection and low rolling resistance.
- Its strong nylon casing and rubber compound guarantee a long service life.



Technical Informations

| Item number | 15212674 |
|------------------------------|-----------------------|
| EAN | 7291050082136 |
| Valid tyre size | 800 / 35 - 22.5 |
| LI / SI / PR | 169 A8 / 162 D, 16 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 128 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 132,68 |
| Recommended rim size | 28.00 |
| Permitted rim size | 24.00, 26.00 |
| Maximum air pressure [bar]. | 2,60 |
| Section width (mm) | 800 |
| Outer diameter of tyre [mm]. | 1170 |
| Stat. radius (SLR) [mm] | 523 |
| Rolling circumference [mm]. | 3508 |
| Tread depth (mm) | 26,0 |
| Number of lugs | 28x2 |
| Tyre capacity 75% [ltr.] | 325 |
| Guarantee period | 7 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 169 A8 | 5800 | 40 | | 2,60 | |
| 162 D | 4750 | 65 | | 2,60 | |