

TYRES

| | |
|-----------------|-----------------------|
| Product group | Tyres |
| Item number | 15212674 |
| Valid tyre size | 800 / 35 - 22.5 |
| LI / SI / PR | 169 A8 / 162 D, 16 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 128 |



Notes and features

- The Alliance 128 was designed for agricultural trailers in the field and on the road.
- The special tread pattern with shoulder lugs provides high traction in the field.
- The grooved tread pattern in the middle of the tread provides comfortable driving performance on roads during transport journeys.
- The tyre enables high loading capacity at low inflation pressure, optimum soil protection and low rolling resistance.
- Its strong nylon casing and rubber compound guarantee a long service life.

Technical Informations

| | |
|------------------------------|-----------------------|
| Item number | 15212674 |
| EAN | 7291050082136 |
| Valid tyre size | 800 / 35 - 22.5 |
| LI / SI / PR | 169 A8 / 162 D, 16 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 128 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 132,68 |
| Recommended rim size | 28.00 |
| Permitted rim size | 24.00, 26.00 |
| Maximum air pressure [bar]. | 2,60 |
| Section width (mm) | 800 |
| Outer diameter of tyre [mm]. | 1170 |
| Stat. radius (SLR) [mm] | 523 |
| Rolling circumference [mm]. | 3508 |
| Tread depth (mm) | 26,0 |
| Number of lugs | 28x2 |
| Tyre capacity 75% [ltr.] | 325 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 169 A8 | 5800 | 40 | | 2,60 | |
| 162 D | 4750 | 65 | | 2,60 | |