

TYRES

Product group	Tyres	
Item number	15223100	
Valid tyre size	480 / 70 - 28	
LI / SI / PR	152 A2 / 145 A8, 14 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agro Forestry 370	



Notes and features

- The Alliance Agro Forestry 370 of the 70 series was designed for agricultural tractors used in the forest and on fields.
- The tyre enables combined work in the field and in the forest without any inflation pressure adaptation.
- The tyre structure maintains the high elastic characteristics that enable high traction in the field and low soil compaction.
- At the same time, the strong nylon casing with steel breakers and the durable rubber compound provide effective damage resistance in forestry applications.
- The Alliance Agro Forestry 370 70 series was developed for tractors working simultaneously in forests and fields.



Technical Informations

Item number	15223100
EAN	7291050046312
Valid tyre size	480 / 70 - 28
LI / SI / PR	152 A2 / 145 A8, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Forestry 370
TRA Code	R1-W
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	124,93
Recommended rim size	15
Maximum air pressure [bar].	2,70
Section width (mm)	479
Outer diameter of tyre [mm].	1448
Stat. radius (SLR) [mm]	668
Rolling circumference [mm].	4334
Tread depth (mm)	46,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A2	3550	10		2,70	
145 A8	2900	40		2,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.